



## Maintenance and Care

### 1. Routine Cleaning

- The high-quality finish of LockersMFG HDPE lockers is very durable and resistant to most products. However, care should be taken to avoid damaging the finish.
  - Acceptable cleaners:
    - Household cleaners such as Lysol, Mr. Clean.
    - Mild soap and detergents such as Dawn, Palmolive, Gain, Tide
    - Mild solvents such as mineral spirits (no acetone or harsh solvents)
    - Household solvent-based cleaners such as Goof Off or Goo Gone
  - Un-acceptable cleaners:
    - Acidic cleaners such as Lime Away, any acid compound
    - Any cleaner containing hydrogen peroxide.
    - Alkaline cleaners such as toilet bowl cleaners.
    - Strong solvents such as acetone, MEK, xylene, etc.
    - Abrasive cleaners include SOS, Comet, Soft Scrub, and any polishing compound.
- After using a cleaning compound, rinse with water and dry with a soft towel or microfiber towel.
- Touch up any scratches immediately to prevent corrosion. Factory-matched touch-up paints are available from LockersMFG. Contact LockersMFG at 662-338-4340 or [info@lockersmfg.com](mailto:info@lockersmfg.com) to get information on matching touch-up paints.

### 2. Annual Maintenance

- Inspect each door for ease of opening and closing
- Note any loose or missing hardware (nuts & bolts, rivets) or accessories (hooks, shelves)
- Ensure latch hooks are centered in latch opening in door and not rubbing. Use pliers to bend into correct position.
- Lubricate latch hooks on door frame.
- Lubricate the latching bar (if applicable) in the door.
- Clean interior and exterior of locker with non-ammonia containing mild cleanser.
- Use a product such as "Goof-Off" or WD-40 to remove any ink or other stains from finish.

### 3. Replacement Parts

- If damage or missing parts are noted and replacements needed, contact LockersMFG at 662-338-4340 or email [info@lockersmfg.com](mailto:info@lockersmfg.com).